SAFETY DATA SHEET

Version: v1

Revision Date: 2023-11-

Print Date: 2023-11-16

SECTION 1:Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : m-Xylylene Diisocyanate

Product Number : M158033
Brand : aladdin
CAS-No. : 3634-83-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Shanghai Aladdin Biochemical Tech Co.,Ltd

Address : 36 Xinjinqiao Road, Shanghai

Telephone : 400-620-6333 Fax : no data available

1.4 Emergency telephone number

Emergency Phone : 0532-83889090

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226

Acute toxicity, Oral (Category 5), H303

Acute toxicity, Inhalation (Category 2), H330

Skin corrosion/irritation (Category 2), H315

Serious eye damage/eye irritation (Category 1), H318

Respiratory sensitization (Category 1), H334

Skin sensitization (Sub-category 1A), H317

Specific target organ toxicity - single exposure, Inhalation (Category 1), Respiratory Tract,

H370

Specific target organ toxicity - repeated exposure, Inhalation (Category 1), Respiratory

Tract, H372

Short-term (acute) aquatic hazard (Category 3), H402

Long-term (chronic) aquatic hazard (Category 3), H412

2.2 GHS Label elements, including precautionary statements

	Pictogram			
--	-----------	--	--	--

Signal word Danger

Hazard	statement	(s)
--------	-----------	-----

H226	Flammable liquid and vapor
H303	May be harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H370 Causes damage to organs

H372 Causes damage to organs through prolonged or repeated exposure

H412 Harmful to aquatic life with long lasting effects

Precautionary statement(s)

P210	Keep away from heat, hot surface, sparks, open flames and other ignition
	sources No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/.../] equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash hands [and ...] thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] Wear respiratory protection.
P310 Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor/...
P333+P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P370+P378 In case of fire: Use ... to extinguish.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : 1,3-Bis(isocyanatomethyl)benzene; Isocyanic Acid 1,3-

Phenylenedimethylene Ester; m-Xylene Diisocyanate; m-Xylylene diisocyanate

Formula : C10H8N2O2

Molecular weight : 188.19

CAS No. : 3634-83-1

EC-NO. : no data available

Component	Classification	Concentration
m-Xylylene Diisocyanate		
	no data available	>98.0%(GC)

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

no data available

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

no data available

5.2 Special hazards arising from the substance or mixture

Carbon oxides Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid)

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material. Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep away from open

flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons. Recommended storage temperature 2 - 8 °C Light sensitive. Store under inert gas. Moisture sensitive. Exposure to moisture.

7.3 Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of Regulation (EU)2016/425 and the standard EN 374 derived from it.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a fullface particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN(EU).

Control of environmental exposure

no data available

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

no data available a) Appearance b) Odour no data available c) Odour Threshold no data available d) pH no data available e) Melting point/freezing point no data available f) Initial boiling point and boiling range no data available g) Flash point no data available no data available h) Evaporation rate i) Flammability (solid, gas) no data available

j) Upper/lower flammability or explosive

no data available limits k) Vapour pressure no data available I) Vapour density no data available m) Relative density no data available n) Water solubility no data available o) Partition coefficient: n-octanol/water no data available p) Auto-ignition temperature no data available q) Decomposition temperature no data available no data available r) Viscosity no data available s) Explosive properties N t) Oxidizing properties N no data available

9.2 Other safety information

no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

no data available

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

Amines, Alcohols, Strong oxidizing agents

10.6 Hazardous decomposition products

no data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 3,200 mg/kg

(OECD Test Guideline 401)

Acute toxicity estimate Inhalation - Expert judgment - 4 h - 0.51 mg/l - vapor

LD50 Dermal - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

Skin corrosion/irritation

no data available

Serious eye damage/eye irritation

no data available

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Specific target organ toxicity - single exposure

Inhalation - Causes damage to organs. - Respiratory Tract

Specific target organ toxicity - repeated exposure

Inhalation - Causes damage to organs through prolonged or repeated exposure. - Respiratory Tract

Aspiration hazard

no data available

Additional Information

RTECS: NR0147000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

no data available

SECTION 13:

13.1 Disposal considerations

Product

Recycle to process, if possible. Consult your local regional authorities and an expert of disposal. You may be able to dissolve or mix material with a combustible solvent and little by little burn in a chemical incinerator equipped with an afterburner and scrubber system. If a large amount of the substance is burned at a time, an explosion may occur. Observe all federal, state and local regulations when disposing of the substance.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 2920 Packing group: II Class: 8 (3)

Proper shipping name: Corrosive liquid, Reportable Quantity(RQ): no data

Poison Inhalation Hazard: no data

flammable, n.o.s. (1,3-Xylylene available available

diisocyanate)

Environmental Hazards: no

IMDG

UN number: 2920 Packing group: II EMS-No: no data available

Proper shipping name: Corrosive liquid, flammable, n.o.s. (1,3-Xylylene diisocyanate)

IATA

UN number: 2920 Packing group: II Class: 8 (3)

Proper shipping name: Corrosive liquid, flammable, n.o.s. (1,3-Xylylene diisocyanate)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

SECTION 16: Other information

07

Further information

Copyright Aladdin Co. Ltd. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Aladdin Co. Ltd. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

Version: v1 Revision Date: 2023-11- Print Date: 2023-11-

16